



stonebranch

Universal Agent 7.3.x

Universal Query 7.3.x Quick Reference Guide

© 2022 by Stonebranch, Inc. All Rights Reserved.

Universal Query 7.3.x Quick Reference Guide

Usage

uquery HOST [OPTIONS...]

Format

There is a long form and, for most options, a short form available for specifying each option on the command line. The long form is not case-sensitive; the short form is case-sensitive. Options must be prefixed with a dash (-) character. If an option value is specified, the option and its value must be separated by at least one space.

HOST -host [-port] [-outboundip]

Long Form	Short Form	Description
-host <i>hostaddress</i>	-i <i>hostaddress</i>	Host network address. <i>hostaddress</i> format is dotted form (1.2.3.4) or host domain name.
-port <i>port</i>	-p <i>port</i>	Host port number on which Universal Broker is listening. Default is 7887.
-outboundip <i>host</i>	n/a	Host network address to bind to for all outbound connections. <i>host</i> format is dotted form (1.2.3.4) or a host domain name.

OPTIONS [{-help |-version }] [-cmdid] [-component] [-lang] [-level] [-codepage] [-ping] [-report] [-bif_directory] [-plf_directory] [-managers] [-system_id]

Long Form	Short Form	Description
-bif_directory <i>directory</i> ^U	n/a	Broker Interface File (BIF) directory where the Universal Broker interface file is located.
-cmdid <i>ID</i>	-C <i>ID</i>	Requests that Universal Query return information for all records that match the specified command ID.
-codepage <i>codepage</i>	-t <i>codepage</i>	Code page used to translate text on the local host.
-component <i>ID</i>	-c <i>ID</i>	Requests that Universal Query return information only for the specified component ID.
-help	-h	Write help file.
-lang <i>language</i>	-L <i>language</i>	Message and text language
-level <i>level</i>	-l <i>level</i>	Message level: error, warn, info, audit, or trace.
-managers <i>option</i>	n/a	Specification for whether or not Universal Query requests manager component information from the queried Broker.
-ping <i>option</i>	-P <i>option</i>	Display only Broker information: yes or no (default).
-plf_directory <i>directory</i> ^U	n/a	Directory where the Program Lock Files (PLF) are located.
-report <i>format</i>	-R <i>format</i>	Report format: fixed or normal (default).
-system_id <i>ID</i> ^Z	n/a	Local Universal Broker with which Universal Query must register before the Universal Query performs any request.
-version	-v	Write program version information and exit.

^U Available for use on UNIX operating systems only.

^Z Available for use on z/OS operating systems only.