

UEMLoad 7.8.x Quick Reference Guide

Universal Agent 7.8.x

© 2024 by Stonebranch, Inc. All Rights Reserved.

Table of Contents

1 Usage.....	4
1.1 uemload [ACTION] [OPTIONS] [{DEFFILE [EVENTDEF] [HANDLER] }].....	4
1.2 uemload { -help -version }	4
2 Format	5
2.1 ACTION { -add -update -delete -list -export }.....	5
2.2 OPTIONS [-port] [-cmdid] [{ -help -version }].....	5
2.3 DEFFILE [-deffile].....	5
2.4 EVENTDEF [-event_id] [-comp_name] [-event_type] [-state] [-act_date_time] [- inact_date_time] [-tracking_int] [-triggered_id] [-rejected_id] [-expired_id] [-handler_opts] [-filespec] [-min_file_size] [-rename_file] [-rename_file_spec]	6
2.5 HANDLER [-handler_id] [-handler_type] [-options] [-maxrc] [-file -encryptedfile [-key]] [- userid [-pwd]] [-cmd -script [-script_type]].....	7

1 Usage

1.1 uemload [ACTION] [OPTIONS] [{DEFFILE | [EVENTDEF] [HANDLER] }]

1.2 uemload { -help | -version }

2 Format

There is a long form and, for most options, a short form available for specifying each option on the command line. The long form is not case-sensitive; the short form is case-sensitive.

Options must be prefixed with a dash (-) character. If an option value is specified, the option and its value must be separated by at least one space.

2.1 ACTION {-add | -update | -delete | -list | -export}

Long Form	Short Form	Description
-add	n/a	Add records to the event definition and/or event handler databases.
-update	n/a	Update records in the event definition and/or event handler databases.
-delete	n/a	Remove records from the event definition and/or event handler databases.
-list	n/a	Displays selected records from the event definition and/or event handler databases.
-export	n/a	Create a definition load file containing selected records from the event definition and/or event handler databases.

2.2 OPTIONS [-port] [-cmdid] [{ -help | -version }]

Long Form	Short Form	Description
-cmdid <i>id</i>	-C <i>id</i>	Command identifier. Associates a Universal Event Monitor Server with the UEMLoad utility that started it.
-help	-h	Write this message.
-level	-l	Level of messages that will be issued.
-port <i>port</i>	-p <i>port</i>	Port number on which the local Universal Broker is listening. If this parameter is omitted, the Universal Broker-installed default is used.
-version	-v	Writes program version information.

2.3 DEFFILE [-deffile]

Long Form	Short Form	Description
-deffile <i>filename</i>	n/a	Complete path to the definition file. This file can be used to specify any number of event definitions and event handlers. When used with the -export option, this is the name of the output file.

2.4 EVENTDEF [-event_id] [-comp_name] [-event_type] [-state] [-act_date_time] [-inact_date_time] [-tracking_int] [-triggered_id] [-rejected_id] [-expired_id] [-handler_opts][[-filespec] [-min_file_size] [-rename_file] [-rename_file_spec]

Long Form	Short Form	Description
-act_date_time <i>date and time</i>	n/a	Date and time at which a UEM Server will begin testing for the occurrence of the specified event. Format for <i>date and time</i> is <i>yyyy.mm.dd,hh:mm</i> . (The time must be expressed in 24-hour format.) <i>date</i> can be omitted, but the comma must be used as a placeholder. If <i>time</i> is omitted, no comma is required.
-comp_name <i>compname</i>	n/a	Name of the UEM Server component to which this event should be assigned.
-event_id <i>id</i>	n/a	Unique identifier of an event definition.
-event_type <i>type</i>	n/a	Type of event. This parameter is required when adding records and updating type-specific values.
-expired_id <i>handlerid</i>	n/a	Event handler to execute when an event expires.
-handler_opts <i>string</i>	n/a	Literal string to pass to an event handler process.
-inact_date_time <i>date and time</i>	n/a	Date and time at which a UEM Server will stop testing for the occurrence of the specified event. Format for <i>date and time</i> is <i>yyyy.mm.dd,hh:mm</i> . (The time must be expressed in 24-hour format.) <i>date</i> can be omitted, but the comma must be used as a placeholder. If <i>time</i> is omitted, no comma is required.
-rejected_id <i>id</i>	n/a	Event handler to execute when an event occurrence is rejected.
-state <i>option</i>	n/a	Used to control whether or not the event is monitored by Universal Event Monitor. Valid values for <i>option</i> are enable and disable.
-tracking_int <i>seconds</i>	n/a	Frequency with which a tracked event is tested for completeness.
-triggered_id <i>handlerid</i>	n/a	Event handler to execute when an event occurrence is triggered.

The following parameters are used when adding or updating event definitions with an event type of **FILE**.

Long Form	Short Form	Description
-filespec <i>filename</i>	n/a	Name of the file whose creation (and completion) Universal Event Monitor should detect. Wildcards can be specified.
-min_file_size <i>size[units]</i>	n/a	Smallest size a file can be in order for UEM to consider it complete. Valid values for <i>unit</i> are (b)ytes, (k)ilobytes, (m)egabytes, and (g)igabytes. If no units are specified, it will default to bytes. If this parameter is omitted, it will default to 0b (zero bytes).
-rename_file <i>option</i>	n/a	Specifies whether or not the file should be renamed before executing the event handler.
-rename_filespec <i>renamefile</i>	n/a	Format to use for the renamed file.

2.5 HANDLER [-handler_id] [-handler_type] [-options] [-maxrc] [-file | -encryptedfile [-key]] [-uerid [-pwd]] [-cmd | -script [-script_type]]

Long Form	Short Form	Description
-cmd <i>command</i>	n/a	Complete path to an application or script that should be executed by the handler.
-encryptedfile <i>filename</i>	-x <i>filename</i>	Universal Encrypted file that contains user account information that will be used for handler execution.
-file <i>filename</i>	-f <i>filename</i>	Complete path to a file that contains user account information that will be used for handler execution.
-handler_id <i>id</i>	n/a	Unique identifier of an event handler.
-handler_type <i>type</i>	n/a	Information that UEM needs when building a command string in order to execute a process for the event handler.
-key <i>key</i>	-k <i>key</i>	Encryption key used to encrypt the file specified by -encryptedfile .
-maxrc <i>returncode</i>	n/a	Highest return code that may be returned by the handler process to still be considered as having executed successfully.
-options	n/a	String value added to the command line that the UEM Server builds in order to execute an event handler process.
-pwd <i>password</i>	-w <i>password</i>	Password for the user account specified by -userid .
-script <i>filename</i>	n/a	File that contains a set of script statements that will be executed by the handler.

Long Form	Short Form	Description
<code>-script_type type</code>	n/a	Type of script provided when the -script option is used. Windows servers treat <i>type</i> as a file extension, which results in the script being executed by the program associated with the extension.
<code>-userid <i>userid</i></code>	<code>-u <i>userid</i></code>	User account in whose security context the event handler process will execute.